

**MECHANICAL SPLICE OPTIONS WITH HIGH STRENGTH REINFORCING BARS**

ASTM A615, A706 GRADE 60		ASTM A615 GRADE 75		ASTM A615, A706 GRADE 80			ASTM A615 GRADE 100	ASTM A1035 GRADE 100		ASTM A1035 GRADE 120	
TYPE 1	TYPE 2	TYPE 1	TYPE 2	TYPE 1	TYPE 2 (A706)	TYPE 2 (A615)	TYPE 2	TYPE 1	TYPE 2	TYPE 1	TYPE 2
75,000 psi	A615 = 90,000 psi A706 = 80,000 psi	93,750 psi	100,000 psi	100,000 psi	A706 = 100,000 psi	A615 = 105,000 psi	115,000 psi	125,000 psi	150,000 psi	150,000 psi	150,000 psi

**MINIMUM STRENGTH REQUIREMENT, ACI 318**

**GRIP-TWIST® SYSTEM**

HIGH STRENGTH TAPER THREADED COUPLERS, SHOP SWAGED BY BP2600 PRESS

<b>STANDARD TAPER THREADED GRIP-TWIST</b>						<b>GRIP-TWIST 'XT'</b>					
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

**ZAP SCREWLOK® SYSTEM**

SHEAR SCREW COUPLERS, FIELD INSTALLED BY IMPACT WRENCH

<b>ZAP 'SL'</b>	<b>ZAP SCREWLOK TYPE 2</b>		<b>ZAP SCREWLOK 'FX'</b>					<b>ZAP SCREWLOK 'FXT'</b>			
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓

**BPI® BARSPLICER SYSTEM**

THREADED STEEL COUPLERS, BARSPLICE SHOP THREADED REBAR

<b>STD BARSPLICER</b>	<b>BARSPLICER XP</b>						<b>100KSI BARSPLICER (CORROSION RESISTANT)</b> [ available substitution for Grade 75 & 80 Type 1 & 2 ]				
✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
[ sizes #4 - #7 (1/2" - 7/8" UNC) ]											

**BARGRIP® XL**

SWAGED COUPLERS, INSTALLED BY FIELD PRESS

✓	✓	✓	✓	✓	✓	✓	VISIT <a href="http://www.barsplice.com">www.barsplice.com</a> FOR ADDITIONAL DETAILS, INCLUDING STATEMENTS, CONDITIONS OF USE, LIMITATIONS, TERMS AND CONDITIONS OF SALE. Copyright © 2013-2015 Barsplice Products, Inc.				
---	---	---	---	---	---	---	--	--	--	--	--

**THIS CHART PROVIDES A GENERAL SUMMARY OF STRENGTH CAPACITIES ONLY WITH UNCOATED REINFORCING BAR & COUPLERS.**