



R- 13 SEP 23

HEADED DEVICE OPTIONS WITH HIGH STRENGTH REINFORCING BARS													
		ASTM A615, A706 GRADE 60		ASTM A615 GRADE 75		ASTM A615, A706 GRADE 80		ASTM A615, A706 GRADE 100		ASTM A1035 GRADE 100		ASTM A1035 GRADE 120	
		ACI 318	ASTM A970	ACI 318	ASTM A970	ACI 318	ASTM A970	ACI 318	ASTM A970		ASTM A970		ASTM A970
MINIMUM STRENGTH REQUIREMENT		100% <i>f_y</i> A615, A706 Grade 60	100% <i>f_u</i> A615, A706 Grade 60	100% <i>f_y</i> A615 Grade 75	100% <i>f_u</i> A615 Grade 75	100% <i>f_y</i> A615, A706 Grade 80	100% <i>f_u</i> A615, A706 Grade 80	100% <i>f_y</i> A615, A706 Grade 100	100% <i>f_u</i> A615, A706 Grade 100	100% <i>f_y</i> A1035 Grade 100	100% <i>f_u</i> A1035 Grade 100	100% <i>f_y</i> A1035 Grade 120	100% <i>f_u</i> A1035 Grade 120
		60,000 psi	80,000 psi	75,000 psi	100,000 psi	80,000 psi	100,000 psi	100,000 psi	117,000 psi	100,000 psi	150,000 psi	120,000 psi	150,000 psi
TAPER THREADED GRIP-TWIST® DOUGHNUT™	HIGH STRENGTH MALE COUPLER, SHOP SWAGED BY BP2600 PRESS, WITH TAPER THREADED DOUGHNUT	STANDARD GRIP-TWIST DOUGHNUT						GRIP-TWIST 'XT' DOUGHNUT					
		✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
BUTTONHEAD	SHOP SWAGED HEADED DEVICE BY BP2600 PRESS	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓	✓
BPI® BARSPLICER DOUGHNUT™	THREADED STEEL DOUGHNUT ON BARSPLICE SHOP THREADED REBAR	STANDARD BARSPLICER	BARSPLICER 'XP' DOUGHNUT						100KSI BARSPLICER DOUGHNUT (CORROSION RESISTANT)				
		✓	✓	✓	✓	✓	✓					✓	
		sizes #4 - #7 (1/2" - 7/8" UNC)						sizes #4 - #7 (1/2" - 7/8" UNC)					
FITT®	FIELD INSTALLED THREADED TERMINATION	✓	✓	✓	✓	✓	✓					THIS CHART PROVIDES A GENERAL SUMMARY OF STRENGTH CAPACITIES WHEN USING BPI HEADED DEVICES ON UNCOATED REINFORCING BAR.	
ZAP SCREWLOK® T-LOK	SHEAR SCREW HEADED DEVICE, FIELD INSTALLED BY IMPACT WRENCH	✓	✓	✓*		✓*		<i>f_y</i> = Specified Yield Strength <i>f_u</i> = Specified Tensile Strength VISIT www.barsplice.com FOR ADDITIONAL DETAILS, INCLUDING STATEMENTS, CONDITIONS OF USE, LIMITATIONS, TERMS AND CONDITIONS OF SALE.					

Copyright © 2023 Barsplice Products, Inc.

- ACI 318 (20.2.2.4, 25.4.4.1) DOES NOT PERMIT HEADED DEVICES ON BAR ABOVE GRADE 80 OR SIZES ABOVE No. 11, HOWEVER IN-AIR TESTING CONFIRMS BPI DEVICES MEET THE EQUIVALENT STRENGTH REQUIREMENTS FOR ALL AVAILABLE SIZES ON BAR GRADES LISTED

* ZAP SCREWLOK T-LOK HEADED DEVICES MEET THE THE MINIMUM SPECIFIED YIELD (*f_y*) OF A615 GRADE 75/80 AND A706 GRADE 80 REINFORCEMENT, AS WELL AS ALL DIMENSIONAL REQUIREMENTS OF ASTM A970.

- ALL BPI HEADED DEVICES ARE AVAILABLE FOR EITHER 4 Ab OR 9 Ab NET (5 Ab OR 10 Ab GROSS) BEARING AREA INSTALLATIONS.